

## Top Tec Truck 6150 5W-30

### Description

High-performance low-friction motor oil with modern wear-protection technology. Ensures high piston cleanliness and a long engine service life. The lower HTHS viscosity allows maximum reduction of fuel consumption while also keeping emissions low. Maintenance costs are minimized thanks to the long oil change intervals.

### Properties

- High stability to aging
- excellent wear resistance
- for heavy-duty Euro 6 bus and commercial vehicle diesel engines
- minimises maintenance costs thanks to long oil change intervals
- ensures long service life of the engine
- high cleaning efficiency
- guarantees low fuel consumption and low emissions

### Specifications / Approvals

API FA-4 • API SN • DTFR 15C130 [228.61] • Volvo VDS-5

**LIQUI MOLY recommends this product for vehicles or assemblies for which the following specifications or original spare part numbers are required:**

Cummins CES 20087 • JASO DH-2 • Detroit Diesel DFS 93K223

### Technical data

SAE class (engine oils)	5W-30 SAE J300
Density at 15 °C	0,860 g/cm <sup>3</sup> DIN 51757
Viscosity at 40 °C	59,0 mm <sup>2</sup> /s ASTM D7042
Viscosity at 100 °C	9,9 mm <sup>2</sup> /s ASTM D7042
Viscosity at -35 °C (MRV)	< 60000 mPas ASTM D4684
Viscosity at -30 °C (CCS)	<= 6600 mPas ASTM D5293
Viscosity index	155 DIN ISO 2909
HTHS at 150°C	2,9 - 3,2 mPas ASTM D5481
Pour point	-45 °C DIN ISO 3016
Evaporation loss (Noack)	10,0 % CEC-L-40-A-93



### Technical data

Flash point	230 °C DIN ISO 2592
Total base number	10,0 mg KOH/g DIN ISO 3771
Sulfate ash	<= 1,0 g/100g DIN 51575
Color number (ASTM)	L 6,5 DIN ISO 2049
Oil base	Advanced Full Synthetic

### Areas of application

For year-round use in high-load Euro 6 commercial vehicle diesel engines, such as in Mercedes-Benz trucks and buses with engine types OM 470, 471, 473, 934, 936, 936h in which a lubricant with these specifications is stipulated. Not backwards compatible, therefore cannot be used in older engines!

### Application

The specifications and instructions from the assembly or vehicle manufacturer must be followed. Optimum effect only when the product is used unmixed.

### Available pack sizes

20 l Canister plastic	21923 D-GB
60 l Black plate barrel	21924 D-GB
205 l Black plate barrel	21907 D-GB

**Our information is based on thorough research and may be considered reliable, although not legally binding.**