

MoS2 Low-Friction 15W-40



Description

Year-round, state-of-the-art motor oil manufactured from selected base oils. The high additive content, which includes the solid lubricant molybdenum disulfide (MoS₂), ensures optimum lubrication under extreme operating conditions and with long oil change intervals.

Properties

- good cold-start behavior
- stable to ageing and stable viscosity
- outstanding engine cleanliness
- outstanding emergency-running properties
- suitable for gasoline and diesel engines with and without exhaust-gas turbocharging
- instant lubrication after cold start
- high wear resistance
- tested for the use with catalytic converters

LIQUI MOLY recommends this product for vehicles or assemblies for which the following specifications or original spare part numbers are required:

ACEA A3 • ACEA B4 • API SL

Technical data

SAE class (engine oils)	15W-40 SAE J300
Density at 15 °C	0,875 g/cm ³ DIN 51757
Viscosity at 40 °C	100,0 mm ² /s ASTM D7042
Viscosity at 100 °C	14,2 mm ² /s ASTM D7042
Viscosity at -25 °C (MRV)	< 60000 mPas ASTM D4684
Viscosity at -20 °C (CCS)	<= 7000 mPas ASTM D5293
Viscosity index	145 DIN ISO 2909
HTHS at 150°C	>= 3,5 mPas ASTM D5481
Pour point	-33 °C DIN ISO 3016
Evaporation loss (Noack)	9,0 % CEC-L-40-A-93
Flash point	230 °C DIN ISO 2592
Total base number	10,4 mg KOH/g DIN ISO 3771
Sulfate ash	1,0 - 1,6 g/100g DIN 51575

Technical data

Color / appearance grau

Areas of application

Motor oil for gasoline, diesel and turbocharged engines. Especially suitable where there are long intervals between oil changes and extreme operating conditions.

Application

The operating materials instructions of the motor vehicle and engine manufacturer must be followed.

Available pack sizes

1 l Canister plastic	2570 AR-BG-CS-DA-EL-EN-ES-FI-FR- HR-HU-IT-KK-NL-NO-PL-PT-RO- RU-SK-SV-TR-ZH
4 l Canister plastic	2631 AR-BG-CS-DA-EL-EN-ES-FI-FR- HR-HU-IT-KK-NL-NO-PL-PT-RO- RU-SK-SV-TR-ZH
5 l Canister plastic	2571 AR-BG-CS-DA-EL-EN-ES-FI-FR- HR-HU-IT-KK-NL-NO-PL-PT-RO- RU-SK-SV-TR-ZH
20 l Canister plastic	2572 DE-EN-ES-IT-PT
60 l Black plate barrel	2573 DE-EN
205 l Black plate barrel	2574 DE-EN

Our information is based on thorough research and may be considered reliable, although not legally binding.